

技术参数:

插芯:

- 插针数: 40+PE
- 额定电流: 10A
- 额定电压: 250V
- 额定脉冲电压: 4kV
- 污染等级: 3
- 依据UL/CSA的额定电压: 600V
- 绝缘阻抗: $\geq 10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数: >500

插针:

- 接线方式: 螺钉连接
- 材料: 铜合金
- 表面处理:
 - 接合侧: 镀银
 - 接线侧: 镀锡
- 接触电阻: $<10\text{m}\Omega$
- 线径范围: $0.2-2.5\text{mm}^2(24-14\text{ AWG})$
- 拧紧/检测力矩: 0.5Nm



Technical specification:

Insters:

- No. of contact: 40+PE
- Rated current: 10A
- Rated voltage: 250V
- Rated impulse voltage: 4kV
- Pollution degree: 3
- Rated voltage acc.to UL/CSA: 600V
- Insulation resistance: $>10^{10}\Omega$
- Material: polycarbonate
- Colour: RAL 7032(light grey)
- Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Mating cycles: >500

Contacts:

- Terminal: screw connection
- Material: copper alloy
- Surface:
 - mating side: hard-silver plated
 - termination side: tin plated
- Contact resistance: $<10\text{m}\Omega$
- Wire gauge: $0.2-2.5\text{mm}^2(24-14\text{ AWG})$
- Tightening/test torque: 0.5Nm



						表面处理 Finish	-			图号 Drawing No.	-
						材料 Material	-			产品代号 Part Code	HD-040-M.AV.L
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date				产品料号 Part No.	1250400110101
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	-
绘图 Drawn	ZM LIN	30.11.2013	标准化 Stand.	-	-	1:2	V1.0	339g	-		
审核 Checked	YY LUO	30.11.2013									
工艺 Process	-	-	批准 Approved	YY LUO	30.11.2013	All Dimensions in mm Original Size DIN A 4			厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD		