






技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: RAL 7037 (灰色)
- 温度范围: -40°C - $+125^{\circ}\text{C}$
- 防护等级: IP65 (联锁状态, IEC 60529)
- 出线方向: 顶出线
- 出线孔数: 1
- 螺纹规格: M32
- 联锁元件:
 - 锁扣方式: 金属双扣
 - 材料: 不锈钢+软胶

Technical specification:

- Material: aluminium die-cast
- Surface: powder-coated
- Colour: RAL 7037(grey)
- Temperature range: -40°C - $+125^{\circ}\text{C}$
- Degree of protection: IP65 (acc.to IEC 60529 for coupled connector)
- Cable entry: top entry
- No. of cable entries: 1
- Thread size: M32
- Locking element:
 - Locking type: double locking latch
 - material: stainless steel+TPR

						表面处理 Finish	—	图号 Drawing No.	—
						材料 Material	—	产品代号 Part Code	W32A-TEH-2L/SC-M32
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date	比例 Scale	版本 REV.	重量 Weight
绘图 Drawn	BQ LUO	18.10.2010	标准化 Stand.	—	—	—	2:3	V1.0	300g
审核 Checked	P RAO	18.10.2010							数量 Qty.
工艺 Process	—	—	批准 Approved	YY LIN	18.10.2010				—
							All Dimensions in mm Original Size DIN A 4		
							 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD		