





- 技术参数:
- 材料: 铜合金
 - 表面处理: 镀银
 - 额定电流: 100A
 - 接触电阻: $\leq 0.3\text{m}\Omega$
 - 线径范围: 35mm^2
 - 最大电缆直径: 14mm
 - 剥线长度: 16mm
 - 可插拔次数: ≥ 500
 - 电缆绞线标准: IEC 60228-5

- Technical specification:
- Material: copper alloy
 - Surface: hard-silver plated
 - Rated current: 100A
 - Contact resistance: $\leq 0.3\text{m}\Omega$
 - Wire gauge: 35mm^2
 - Max. insulation diameter: 14mm
 - Stripping length: 16mm
 - Mating cycles: ≥ 500
 - For stranded fine wire acc. to: IEC 60228-5



						表面处理 Finish		—		图号 Drawing No.	—
						材料 Material		—		产品代号 Part Code	CKSF-35G
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date				产品料号 Part No.	1010261201703
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	—
绘图 Drawn	BQ LUO	18.10.2010	标准化 Stand.	—	—	2:1	V1.2	21.2g	—		
审核 Checked	P RAO	18.10.2010									
工艺 Process	—	—	批准 Approved	YY LIN	18.10.2010			All Dimensions in mm Original Size DIN A 4		 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	