



技术参数:

- 材料: 铜合金
- 表面处理: 镀银
- 额定电流: 650A
- 接触电阻: $\leq 0.3\text{m}\Omega$
- 线径范围: 240mm^2
- 最大电缆直径: 32mm
- 可插拔次数: ≥ 500
- 压力要求: 130kN

Technical specification:

- Material: copper alloy
- Surface: hard-silver plated
- Rated current: 650A
- Contact resistance: $\leq 0.3\text{m}\Omega$
- Wire gauge: 240mm^2
- Max. insulation diameter: 32mm
- Mating cycles: ≥ 500
- Pressing force requirement: 130kN

						表面处理 Finish	—				图号 Drawing No.	—
						材料 Material	—				产品代号 Part Code	CHSF650—240G
											产品料号 Part No.	1010301202403
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	—
	姓名/Name	日期/Date			姓名/Name	日期/Date						
绘图 Drawn	BQ LUO	07.05.2018	标准化 Stand.		—	—	2:3	V1.2	211g	—	 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	
审核 Checked	HZ LAN	07.05.2018										
工艺 Process	—	—	批准 Approved	HQ ZHANG	07.05.2018	 	All Dimensions in mm Original Size DIN A 4					