

	日期/Date	档案员 Filing Clerk	1	2	3	4	5	6
D								
C								
B								
A								

Technical drawing of a cable connector. The side view shows a cylindrical body with a central bore. The outer diameter is 11.5mm, and the inner diameter is 7mm. The length of the central bore is 15.5mm. The total length of the component is 31.5mm. A perspective view shows the connector's profile.

技术参数:

- 材料: 铜合金
- 表面处理: 镀银
- 额定电流: 70A
- 接触电阻: $\leq 0.5\text{m}\Omega$
- 线径范围: 25mm^2
- 最大电缆直径: 11mm
- 剥线长度: 15.5mm
- 可插拔次数: ≥ 500
- 电缆绞线标准: IEC 60228-5

Technical specification:

- Material: copper alloy
- Surface: hard-silver plated
- Rated current: 70A
- Contact resistance: $\leq 0.5\text{m}\Omega$
- Wire gauge: 25mm^2
- Max. insulation diameter: 11mm
- Stripping length: 15.5mm
- Mating cycles: ≥ 500
- For stranded fine wire acc. to: IEC 60228-5

						表面处理 Finish	—			图号 Drawing No.	—	
						材料 Material	—			产品代号 Part Code	CKSF70-25	
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品料号 Part No.	1010341101601
绘图 Drawn	BQ LUO	18.10.2010	标准化 Stand.	—	—	2:1	V1.1	9g	—	产品名称 Part Name	—	
审核 Checked	P RAO	18.10.2010										
工艺 Process	—	—	批准 Approved	YY LIN	18.10.2010			All Dimensions in mm Original Size DIN A 4			 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	

1	2	3	4	5	6
---	---	---	---	---	---