

1 | 2 | 3 | 4 | 5 | 6

ad

产品料号 Part NO.	螺纹规格AG Thread size	板子尺寸SW Wrench size	厚度H Thickness	重量/Weight g
1021060112102	M12*1.5	19	5	1
1021060132102	M16*1.5	22	5	1.2
1021060142102	M18*1.5	24	5	1.6
1021060152102	M20*1.5	27	6	2.2
1021060162102	M22*1.5	30	6	2.8
1021060172102	M24*1.5	30	6	3
1021060182102	M25*1.5	32	7	3.1
1021060192102	M32*1.5	40	7	4.7
1021060202102	M40*1.5	49	8	7.5
1021060462102	M50*1.5	60	8	14.3
1021060482102	M63*1.5	75	8	12.3



--	--	--	--	--	--

产品型号 Part NO.	螺纹规格AG Thread size	扳子尺寸SW Wrench size	厚度H Thickness	重量/Weight g
1021060012102	PG7	19	5	1.2
1021060022102	PG9	21	5	1.35
1021060032102	PG11	24	5	2
1021060042102	PG13.5	27	6	2.1
1021060052102	PG16	30	6	2.4
1021060062102	PG21	36	7	3.8
1021060072102	PG29	45	7	5.8
1021060082102	PG36	60	8	12.6
1021060092102	PG42	65	8	15
1021060102102	PG48	69.5	8	16.8



— 材料:

• 主体: 尼龙66

- 温度范围: -40°C — 100°C , 短时间可以达到 120°C

- Material:

- Body: polyamide

- Temperature range: -40°C – 100°C , short-term 120°C

A