

日期/Date

档案员
Filing Clerk

1




2

3

4

5

6



技术参数:

- 材料: 压铸锌
- 表面处理: 粉末喷涂
- 颜色: RAL 7037 (灰色)
- 温度范围: -40°C - $+125^{\circ}\text{C}$
- 防护等级: IP65 (联锁状态, IEC 60529)
- 出线方向: 顶出线
- 出线孔数: 1
- 螺纹规格: M20*1.5
- 联锁元件:
 - 锁扣方式: 单扣
 - 材料: 不锈钢

Technical specification:

- Material: zinc die-cast
- Surface: powder-coated
- Colour: RAL 7037(grey)
- Temperature range: -40°C - $+125^{\circ}\text{C}$
- Degree of protection: IP65
(acc.to IEC 60529 for coupled connector)
- Cable entry: top entry
- No. of cable entries: 1
- Thread size: M20*1.5
- Locking element:
 - Locking type: single locking latch
 - material: stainless steel

						表面处理 Finish	—			图号 Drawing No.	—	
										材料 Material	—	
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date				产品料号 Part No.		
	姓名/Name	日期/Date			姓名/Name	日期/Date				比例 Scale	版本 REV.	重量 Weight
绘图 Drawn	L CHEN	27.09.2020	标准化 Stand.		—	—	1:1	V1.1	109g	—		
审核 Checked	HZ LAN	27.09.2020										
工艺 Process	—	—	批准 Approved	HQ ZHANG	27.09.2020		All Dimensions in mm Original Size DIN A 4				厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	