





- 材料: 压铸铝
- 表面处理: 耐腐蚀涂料
- 颜色: RAL 9005 (黑色)
- 温度范围: -40℃ - +125℃
- 防护等级: IP65
- 出线方向: 侧出线
- 出线孔数: 1
- 螺纹规格: PG21
- 联锁元件:
 - 锁扣方式: 金属双扣
 - 材料: 不锈钢+橡胶
- 密封元件: FPM

- Material: aluminium die-cast
- Surface: corrosion resistant
- Colour: RAL 9005(black)
- Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Degree of protection: IP65
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: PG21
- Locking element:
 - Locking type: double locking latch
 - material: stainless steel+TPR
- Hoods/Housings sealing: FPM

					表面处理 Finish	—				图号 Drawing No.	—
					材料 Material	—				产品代号 Part Code	H24B-MSFH-2L/SC-PG21
标记 Mark	处数 Number	变更描述/Description		签名 Signature		日期 Date	—				产品料号 Part No.
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	—
绘图 Drawn	ZH ZHANG	10.08.2022	标准化 Stand.	—	—	1:2	V1.0	286g	—		
审核 Checked	Q GAO	10.08.2022									
工艺 Process	—	—	批准 Approved	HQ ZHANG	10.08.2022	 		All Dimensions in mm Original Size DIN A 4		 厦门唯思电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	