





- 材料：压铸铝
- 盖子材料：PC
- 表面处理：粉末喷涂
- 颜色：RAL 7037（灰色）
- 温度范围：-40℃ - +125℃
- 防护等级：IP65（联锁状态,IEC 60529）
- 密封元件：NBR
- 出线方向：侧出线
- 出线孔数：2
- 螺纹规格：2PG16

- Material: aluminium die-cast
- Material,cover: PC
- Surface: powder-coated
- Colour: RAL 7037(grey)
- Temperature range: -40°C - $+125^{\circ}\text{C}$
- Degree of protection: IP65
(acc.to IEC 60529 for coupled connector)
- Hoods/Housings sealing: NBR
- Cable entry: side entry
- No. of cable entries: 2
- Thread size: 2PG16

						表面处理 Finish				—	图号 Drawing No.	—	
						材料 Material				—		产品代号 Part Code	HV10B-SF-4B-CV-2PG16
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date						产品料号 Part No.	1240102701030
绘图 Drawn	姓名/Name	日期/Date	标准化 Stand.	姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	—		
	BQ LUO	18.10.2010				1:2	V1.1	255g	—				
审核 Checked	P RAO	18.10.2010											
工艺 Process	—	—	批准 Approved	YY LIN	18.10.2010	 		All Dimensions in mm Original Size DIN A 4		 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD			