




- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: RAL 7037 (灰色)
- 温度范围: -40℃ - +125℃
- 防护等级: IP65 (联锁状态, IEC 60529)
- 密封元件: NBR
- 出线方向: 侧出线
- 出线孔数: 1
- 螺纹规格: PG29

Technical specification:

- Material: aluminium die-cast
- Surface: powder-coated
- Colour: RAL 7037(grey)
- Temperature range: -40°C - +125°C
- Degree of protection: IP65
(acc.to IEC 60529 for coupled connector)
- Hoods/Housings sealing: NBR
- Cable entry: side entry
- No. of cable entries: 1
- Thread size: PG29

						表面处理 Finish	—			图号 Drawing No.	—	
						材料 Material	—			产品代号 Part Code	HV16B-SFH-4B-PG29	
标记 Mark	处数 Number	变更描述/Description			签名 Signature		日期 Date	—			产品料号 Part No.	1240162305012
	姓名/Name	日期/Date		姓名/Name	日期/Date		比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	—
绘图 Drawn	SL CHEN	18.10.2010	标准化 Stand.	—	—		2:3	V1.1	402g	—		
审核 Checked	P RAO	18.10.2010				 	All Dimensions in mm Original Size DIN A 4			 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD		
工艺 Process	—	—	批准 Approved	YY LIN	18.10.2010							