





技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: RAL 7037 (灰色)
- 温度范围: -40℃ - +125℃
- 防护等级: IP65 (联锁状态, IEC 60529)
- 联锁元件:
 - 锁扣方式: 金属双扣
 - 材料: 不锈钢+软胶
- 密封元件: NBR
- 出线方向: 侧出线
- 出线孔数: 2
- 螺纹规格: 2PG29

Technical specification:

- Material: aluminium die-cast
- Surface: powder-coated
- Colour: RAL 7037(grey)
- Temperature range: -40℃ - +125℃
- Degree of protection: IP65
(acc.to IEC 60529 for coupled connector)
- Locking element:
 - Locking type: double locking latch
 - material: stainless steel+TPR
- Hoods/Housings sealing: NBR
- Cable entry: side entry
- No. of cable entries: 2
- Thread size: 2PG29

						表面处理 Finish		图号 Drawing No.	
						材料 Material		产品代号 Part Code	
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date	比例 Scale		产品料号 Part No.
绘图 Drawn	姓名/Name		日期/Date	标准化 Stand.	姓名/Name		版本 REV.	重量 Weight	数量 Qty.
	审核 Checked		日期/Date		日期/Date		1:2	V1.1	461g
工艺 Process		批准 Approved		YY LIN		18.10.2010	All Dimensions in mm Original Size DIN A 4		产品名称 Part Name
								厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	