







面板安装开孔图
Panel cut out



技术参数:

插芯:

- 插针数: 40+PE
- 额定电流: 10A
- 额定电压: 250V
- 额定脉冲电压: 4kV
- 污染等级: 3
- 依据UL/CSA的额定电压: 600V
- 绝缘阻抗: $>10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围: -40°C - $+125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数: >500

插针:

- 接线方式: 冷压连接
- 材料: 铜合金
- 表面处理:
 - 镀银
 - 镀金
- 接触电阻: $\leq 3\text{m}\Omega$
- 线径范围: $0.14-2.5\text{mm}^2$ (26-14 AWG)
- 工具:
 - 冷压钳: TL02G
 - 退针器: TL00

Technical specification:

Insters:

- No. of contact: 40+PE
- Rated current: 10A
- Rated voltage: 250V
- Rated impulse voltage: 4kV
- Pollution degree: 3
- Rated voltage acc.to UL/CSA: 600V

- Insulation resistance: $\geq 10^{10}\Omega$

- Material: polycarbonate

- Colour: RAL 7032 (light grey)

- Temperature range: -40°C - $+125^{\circ}\text{C}$

- Flammability acc.to UL 94: V0

- Mating cycles: ≥ 500

Contacts:

- Terminal: crimp terminal

- Material: copper alloy

Surface:


- Hard-silver plated
- Hard-gold plated

- Contact resistance: $\leq 3\text{m}\Omega$

- Wire gauge: $0.14-2.5\text{mm}^2$ (26-14 AWG)

Tools:

- Crimp contact tool: TL02G
- Contact removal tool: TL00

						表面处理 Finish		—		图号 Drawing No.	—
						材料 Material		—		产品代号 Part Code	HD-040-MC Z
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date				产品料号 Part No.	1250400100002
绘图 Drawn	姓名/Name	日期/Date	标准化 Stand.	姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	—
	YL GAO	02.12.2023				1:1	V1.1	54.4g	—		
审核 Checked	Q GAO	02.12.2023									
工艺 Process	—	—	批准 Approved	HQ ZHANG	02.12.2023			All Dimensions in mm Original Size DIN A 4		 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	