


技术参数:

插芯:

- 插针数: 3/2+PE
- 额定电流:
 - 电力区: 200A
 - 信号区: 16A
- 额定电压:
 - 电力区: 1150V/2000V
 - 信号区: 400V
- 额定脉冲电压:
 - 电力区: 8kV
 - 信号区: 6kV
- 污染等级: 3
- 绝缘阻抗: $>10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围: $-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数: >500

插针:

- 接线方式: 轴向螺栓连接
- 材料: 铜合金
- 表面处理: 镀银
- 接触电阻: $\leq 0.2\text{m}\Omega$
- 电缆绞线依据: IEC 60 228-5
- 线径范围:
 - 强电针: $35-70\text{mm}^2(2-00\text{ AWG})$
 - 接地针: $16-35\text{mm}^2(5-2\text{ AWG})$
 - 信号针: $2.5\text{mm}^2(14\text{ AWG})$
- 内六角扳手:
 - 强电针: SW5
 - 接地针: SW4
- 剥线长度:
 - 强电针: 22mm
 - 接地针: 14mm
 - 信号针: 7mm
- 拧紧力矩:
 - 强电针:
 - mm^2 : 35 50 70
 - N·m: 8 9 10
 - 接地针: 6N·m
 - 信号针: 0.5N·m

Technical specification:

Insters:

- No. of contact: 3/2+PE
- Rated current:
 - Power area: 200A
 - Signal area: 16A
- Rated voltage:
 - Power area: 1150V/2000V
 - Signal area: 400V
- Rated impulse voltage:
 - Power area: 8kV
 - Signal area: 6kV
- Pollution degree: 3
- Insulation resistance: $\geq 10^{10}\Omega$
- Material: polycarbonate
- Colour: RAL 7032(light grey)
- Temperature range: $-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Mating cycles: ≥ 500
- Contacts:
 - Terminal: axial screw terminal
 - Material: copper alloy
 - Surface: hard-silver plated
 - Contact resistance: $\leq 0.2\text{m}\Omega$
 - For stranded wire acc. to: IEC 60 228-5
 - Wire gauge:
 - Power contacts: $35-70\text{mm}^2(2-00\text{ AWG})$
 - PE contacts: $16-35\text{mm}^2(5-2\text{ AWG})$
 - Signal contacts: $2.5\text{mm}^2(14\text{ AWG})$
- Hexagonal driver:
 - Power contacts: SW5
 - PE contacts: SW4
- Stripping length:
 - Power contacts: 22mm
 - PE contacts: 14mm
 - Signal contacts: 7mm
- Tightening tourque:
 - Power contacts:
 - mm^2 : 35 50 70
 - N·m: 8 9 10
 - PE contacts: 6N·m
 - Signal contacts: 0.5N·m

						表面处理 Finish	—			图号 Drawing No.	—	
						材料 Material	—			产品代号 Part Code	HK-003/2-M	
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品料号 Part No.	1280050110001
绘图 Drawn	BQ LUO	18.10.2010	标准化 Stand.	—	—	1:2	V1.0	293.12g	—	—	产品名称 Part Name	—
审核 Checked	P RAO	18.10.2010	—	—	—	—	—	—	—	—	—	—
工艺 Process	—	—	批准 Approved	YY LIN	18.10.2010	—	—	—	—	—	—	—
							—	—	All Dimensions in mm Original Size DIN A 4			
							—	—	XIAMEN WAIN ELECTRICAL CO.,LTD			