



- 插针数: 4
- 额定电流: 1A
- 额定电压: 50V
- 额定脉冲电压: 0.8kV
- 污染等级: 3
- 依据UL的额定电压: <30V
- 绝缘阻抗: $>10^{10}\Omega$
- 工作温度范围: -40°C - $+85^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数: >500

- No. of contact: 4
- Rated current: 1A
- Rated voltage: 50V
- Rated impulse voltage: 0.8kV
- Pollution degree: 3
- Rated voltage acc.to UL: <30V
- Insulation resistance: $\geq 10^{10} \Omega$
- Temperature range: $-40^{\circ}\text{C} - +85^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Mating cycles: ≥ 500

					表面处理 Finish	—				图号 Drawing No.	—	
					材料 Material	—				产品代号 Part Code	HM-USB-F	
标记 Mark	处数 Number	变更描述/Description		签名 Signature		日期 Date					产品料号 Part No.	1290010020093
	姓名/Name	日期/Date		姓名/Name		日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	—
绘图 Drawn	CY WU	27.02.2017	标准化 Stand.	—		—	1:1	V1.0	4.91g	—		
审核 Checked	ZW WU	27.02.2017										
工艺 Process	—	—	批准 Approved	YY LOU	27.02.2017	  All Dimensions in mm Original Size DIN A 4			 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD			