

日期/Date

档案员
Filing Clerk

1




2

3

4

5

6



技术参数:

插芯:

- 插针数: 3
- 额定电流: 40A
- 额定电压: 690V
- 额定脉冲电压: 8kV
- 污染等级: 3
- 依据UL的额定电压: 600V
- 绝缘阻抗: $\geq 10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数: ≥ 500

插针:

- 接线方式: 轴向螺栓连接
- 材料: 铜合金
- 表面处理: 镀银
- 接触电阻: $\leq 1\text{m}\Omega$
- 线径范围: 6-10mm²
- 内六角扳手: SW-2*40
- 剥线长度:
 - mm²: 2.5 4 6 10
 - mm: 5⁺¹ 5⁺¹ 8⁺¹ 11⁺¹
- 拧紧力矩:
 - mm²: 2.5 4 6 10
 - N·m: 1.5 1.5 2 2

Technical specification:

Inserts:

- No. of contact: 3
- Rated current: 40A
- Rated voltage: 690V
- Rated impulse voltage: 8kV
- Pollution degree: 3
- Rated voltage acc.to UL: 600V
- Insulation resistance: $\geq 10^{10}\Omega$
- Material: polycarbonate
- Colour: RAL 7032(light grey)
- Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Mating cycles: ≥ 500

Contacts:

- Terminal: axial screw terminal
- Material: copper alloy
- Surface: hard-silver plated
- Contact resistance: $\leq 1\text{m}\Omega$
- Wire gauge: 6-10mm²
- Hexagonal driver: SW-2*40
- Stripping length:
 - mm²: 2.5 4 6 10
 - mm: 5⁺¹ 5⁺¹ 8⁺¹ 11⁺¹
- Tightening torque:
 - mm²: 2.5 4 6 10
 - N·m: 1.5 1.5 2 2

						表面处理 Finish	—		图号 Drawing No.	—
						材料 Material	—		产品代号 Part Code	HMK-003.2-F
标记 Mark	处数 Number	变更描述/Description			签名 Signature				产品料号 Part No.	1290030210002
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name
绘图 Drawn	BQ LUO	18.10.2010	标准化 Stand.	—	—	1:1	V1.0	30.2g	—	—
审核 Checked	P RAO	18.10.2010								
工艺 Process	—	—	批准 Approved	YY LIN	18.10.2010			All Dimensions in mm Original Size DIN A 4		 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD