


- 插针数: 4
- 额定电流(40℃): 4A
- 额定电压: 30V
- 额定脉冲电压: 800V
- 污染等级: 3
- 接触电阻: $\leq 10\text{m}\Omega$
- 绝缘电阻: $\geq 100\text{M}\Omega$
- 锁紧方式: 螺纹式M8*1
- 电缆类型: PUR, 黑色RAL9005
- 线规: 0.25mm^2
- 防护等级: IP67
- 插拔次数: ≥ 100
- 温度范围: $-25^{\circ}\text{C} \dots +85^{\circ}\text{C}$
- 外壳材料: TPU
- 插体材料: PA
- 插针材料: 铜合金
- 电镀材料: 金

- Number of contacts: 4
- Rated current (40°C): 4A
- Rated voltage: 30V
- Rated impulse voltage: 800V
- Pollution degree: 3
- Contact resistance: $\leq 10\text{m}\Omega$
- Insulation resistance: $\geq 100\text{M}\Omega$
- Connector locking system: screw M8*1
- Cable type: PUR , Black RAL 9005
- Wire gauge: 0.25mm^2
- Degree of protection: IP67
- Mating cycles: ≥ 100
- Temperature range: $-25^\circ\text{C} \dots +85^\circ\text{C}$
- Material of housing: TPU
- Material of insert: PA
- Material of contact: copper alloy
- Contact plating: Au



4Pin



•

— 黑色black

厦门唯恩电气有限公司
XIAMEN WAIN ELECTRICAL CO.,LTD