




插针数 Contacts	料号 Order No.	产品代号 Part Code	电缆直径(D) Cable outlet	重量 Weight
4	1630045211003	M12S-F04B-S-D6	4-6mm	26.5g
	1630045211004	M12S-F04B-S-D8	6-8mm	26.3g
5	1630055211004	M12S-F05B-S-D6	4-6mm	28.2g
	1630055211005	M12S-F05B-S-D8	6-8mm	28g

技术参数:

- 产品系列: M12-B 编码
- 插针数: 4 5
- 额定电流(40℃): 4A 4A
- 额定电压: 250V 125V
- 额定脉冲电压: 2500V 1500V
- 污染等级: 3
- 接触电阻: $\leq 10\text{m}\Omega$
- 防护等级: IP67
- 插拔次数: > 100
- 温度范围: $-40^{\circ}\text{C} \dots +85^{\circ}\text{C}$
- 绝缘阻抗: $> 100\text{M}\Omega$
- 接线方式: 螺钉锁紧
- 线径范围: $\text{max.}0.75\text{mm}^2$ (max.AWG18)
- 锁紧扭矩: 0.2Nm (螺钉接线)
- 电缆直径: 4-6mm, 6-8mm
- 电缆剥线长度: 20mm
- 导线剥线长度: 5mm

材料特性:

- 锁紧螺帽: 不锈钢
- 插针材料: 铜合金
- 插针表面处理: 镀金
- 外壳材料: PA
- 颜色: RAL 9005 (黑色)
- 绝缘材料: PA

Technical specification:

- Series: M12 B-Code
- Number of contacts: 4 5
- Rated current(40℃): 4A 4A
- Rated voltage: 250V 125V
- Rated impulse voltage: 2500V 1500V
- Pollution degree: 3
- Contact resistance: $\leq 10\text{m}\Omega$
- Degree of protection: IP67
- Mating cycles: > 100
- Temperature range: $-40^{\circ}\text{C} - +85^{\circ}\text{C}$
- Insulation resistance: $\geq 100\text{M}\Omega$
- Termination method: screw connection
- Wire gauge: $\text{max.}0.75\text{mm}^2$ (max.AWG18)
- Torque: 0.2Nm (screw terminal blocks)
- Cable Outlet: 4~6mm, 6-8mm
- Stripping length of the sheath: 20mm
- Stripping length of the individual wire: 5mm

Material properties :

- Material of locking system: Stainless steel
- Material of contact: copper alloy
- Contact plating: Au
- Material of housing : PA
- Colour of housing: RAL 9005 (Black)
- Material of Insert: PA


符合标准: IEC 61076-2-101

Standards: IEC 61076-2-101

针位排布图

Contact arrangement

3-pole	4-pole	5-pole



						表面处理 Finish	—	图号 Drawing No.	—
						材料 Material	—	产品代号 Part Code	M12S-F0xB-S-Dx
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date		产品料号 Part No.	—
绘图 Drawn	姓名/Name	日期/Date	标准化 Stand.		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight
审核 Checked	ZH SU	18.12.2020			—	—	1:1	V1.0	数量 Qty.
工艺 Process	—	—	批准 Approved	HQ ZHANG	18.12.2020				
							比例 Scale	版本 REV.	重量 Weight
							1:1	V1.0	—
							数量 Qty.	—	—
							All Dimensions in mm Original Size DIN A 4		
							厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD		