

日期/Date	图号	图例	1	2	3	4	5	6	
技术参数:			插针数 Contacts		电缆出口直径Ø Cable outlet	产品料号 Cable outlet	型号 Part Code	重量 Weight	针位图 Contact arrangements
- 产品系列: 7/8			4(3+PE)		6-8 mm	1680045113001	7/8-M04-S-D8	55g	
- 插针数: 4(3+PE)					8-10 mm	1680045113002	7/8-M04-S-D10	55g	
- 插针分布: 3+PE					10-12 mm	1680045113003	7/8-M04-S-D12	55g	
- 插针直径(mm): Ø1.95									
- 接线范围(mm²/AWG): Max1.5mm²/AWG16									
- 接线方式: 螺钉连接									
- 额定电流(40℃): 9A									
- 额定电压: 300V									
- 额定脉冲电压: 4KV									
- 过电压保护等级: III									
- 污染等级: 3									
机械参数:									
- 外壳材质: 铜合金,PA									
- 外壳表面处理: 镀镍									
- 插芯材质: TPU、PA									
- 密封材质: 氟橡胶									
- 温度范围: -25℃...+85℃									
- 电缆直径: Ø6-12mm									
- 插拔次数: >100									
- 防护等级: IP67									
Technical specification:									
- Series: 7/8									
- Number of contacts: 4(3+PE)									
- Contact arrangement: 3+PE									
- Contact diameter(mm): Ø1.95									
- Wire gauge(mm²/AWG): Max1.5mm²/AWG16									
- Terminal: Screw									
- Rated current(40℃): 9A									
- Rated voltage: 300V									
- Rated impulse voltage: 4KV									
- Overvoltage category: III									
- Pollution degree: 3									
Mechanical specification:									
- Material of housing: CuZn,PA									
- Finish of housing: Nickel-plated									
- Material of Insert: TPU、PA									
- Material of sealing: FPM									
- Temperature range: -25℃...+85℃									
- Cable Outlet: Ø6-12mm									
- Mating cycles: >100									
- Degree of protection: IP67									