

技术参数:

- 产品系列: MR23
- 插针数: 6/7
- 插针直径(mm) : $\phi 2$
- 接线范围(mm²/AWG): 0.35-2.5/AWG22-14
- 接线方式: 冷压连接
- 额定电流(25℃): 20A
- 额定电压: 110V
- 额定脉冲电压: 2.5KV
- 过电压保护等级: III
- 污染等级: 3
- 插针需单独订购.

机械参数:



- 外壳材质: 铜合金, 锌合金
- 外壳表面处理: 镀镍
- 插芯材质: PBT
- 密封材质: 氟橡胶
- 温度范围: -40℃...+130℃
- 插拔次数: >500
- 防护等级: IP67

Technical specification:


- Series: MR23
- Number of contacts: 6/7
- Contact diameter(mm): $\phi 2$
- Wire gauge(mm²/AWG): 0.35-2.5/AWG22-14
- Terminal: Crimp
- Rated current(25℃): 20A
- Rated voltage: 110V
- Rated impulse voltage: 2.5KV
- Overvoltage category: III
- Pollution degree: 3

Mechanical specification:

- Material of housing: CuZn,Zinc(GD-Zn)
- Finish of housing:Nickel-plated
- Material of Insert:PBT
- Material of sealing:FPM
- Temperature range: -40℃...+130℃
- Mating cycles: >500
- Degree of protection: IP67
- Contact need to be ordered separately.



针位排布图	针位排布图	针位排布图	针位排布图
Contact arrangement	Contact arrangement	Contact arrangement	Contact arrangement
006 R	007 R	006	007



插针数 Contacts	产品料号 Cable outlet	型号 Part Code	重量 Weight
6	1810063003005	MR23-006-BK-M20	27.22g
7	1810073003005	MR23-007-BK-M20	27.22g
6	1810063003006	MR23-006R-BK-M20	27.22g
7	1810073003006	MR23-007R-BK-M20	27.22g
-	-	MR23-XXX-BK-M20	-g

						表面处理 Finish		—		图号 Drawing No.	
						材料 Material		—		产品代号 Part Code	MR23-XXX-BK-M20
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date				产品料号 Part No.	—
绘图 Drawn	姓名/Name	日期/Date	标准化 Stand.	姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	—
审核 Checked	ZQ XU	29.03.2022				1:1	V1.0	-g	—		
工艺 Process	—	—	批准 Approved	HQ ZHANG	29.03.2022			All Dimensions in mm Original Size DIN A 4		 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	